

HOME

GROUP 4

CORROSION
PROTECTION

CONTENTS

BODY SEALING LOCATIONS	4-2	UNDERCOAT APPLICATION LOCATIONS	4-7
ANTICORROSION PRIMER LOCATIONS	4-6		


BODY SEALING LOCATIONS

M4040001000677

NOTES WITH REGARD TO REPAIR WORK


In place where the sealant can be directly seen on surfaces such as the drip rails, pillars, or clinch, and where the appearance of the paint surface is important, apply sealant or wipe away sealant after application to make the amount of sealant even. Be careful not to cover the drain hole. Places indicated by thick dashed lines indicate application locations on the under side of the vehicle.

FLOOR




AB501177AB

UPPER BODY















AB501178AB








SIDE BODY



AB501179AB







ANTICORROSION PRIMER LOCATIONS

M4040002000421

To prevent rusting from chipping (flying rock), a priming panel primer has been applied to the areas indicated in the figure.


The priming panel primer is applied between the under and middle coat. It improves anti-corrosive performance by preventing flying rock to damage the body panel with the primer application, according to the thickness and elasticity of the primer. Apply the primer before the middle coat when replacing the panel complete with a priming panel primer application.

Primer: Rocker panel primer


Recommended primer:

**Glasurit FX89-7300 (Polyester basis) or
FX90-7103 (Water basis) or equivalent**

Coating thickness: 0.3 mm or more



A



A

■ : Rocker panel primer
*:Coating thickness 0.2 ± 0.05 mm

AB501512AB


UNDERCOAT APPLICATION LOCATIONS

M4040003000480

The under parts of the body is undercoated for anti-corrosive, anti-rust, anti-chipping, and anti-vibration performance.

After correcting the body, restore as shown in the instructions of the figure, if necessary.

Tape the areas marked with an asterisks to protect those areas from getting any undercoating on those areas for parts attachment.



: Undercoat [Film thickness of at least 0.8 mm]

AB501127AB