

## GROUP 33

# FRONT SUSPENSION

## GENERAL

### OUTLINE OF CHANGE

The specifications of the coil spring has been changed.

## GENERAL INFORMATION

### SPECIFICATIONS

#### COIL SPRING

<Vehicles for General export short wheelbase (except for GCC-GL and 3200) and Long wheelbase-3000>

Item	New	Old (for reference)
Wire diameter × average diameter × free length mm	16 × (89 – 109) × 317	17 × 110 × 317

<Vehicle for GCC-short wheelbase (GL)>

Item	New	Old (for reference)
Wire diameter × average diameter × free length mm	16 × (89 – 109) × 313	16 × 109 × 318

<3200 (except for Australia-GLX and GLS)>

Item	New	Old (for reference)
Wire diameter × average diameter × free length mm	16 × (89 – 109) × 326	17 × (90 – 110) × 326

<Vehicles for long wheelbase-2800 and Australia-3200 (GLX and GLS)>

Item	New	Old (for reference)
Wire diameter × average diameter × free length mm	16 × (89 – 109) × 321	16 × 109 × 327

<Vehicles for General export-long wheelbase-3800 (GLS and EXCEED)>

Item	New	Old (for reference)
Wire diameter × average diameter × free length mm	16 × (89 – 109) × 326	16 × 109 × 327

<3500, General export-long wheelbase-3800 (except for GLS and EXCEED)>

Item	New	Old (for reference)
Wire diameter × average diameter × free length mm	16 × (89 – 109) × 322	16 × 109 × 322